

## DS-7304/08/16HQHI-SH

### Series DVR

#### Introduction:

DS-7300HQHI-SH series DVR (Digital Video Recorder) is a new generation recorder developed by Hikvision independently which can connect HD analog/network cameras and Coaxitron cameras and provide powerful surveillance. Combined with multiple advanced technologies, such as audio and video encoding & decoding technology, embedded system technology, storage technology, network technology and intelligent technology. It can both work alone as a recorder and cooperate with other devices to build a comprehensive surveillance system.

The DS-7300HQHI-SH series DVR are widely applied in the areas of finance, public security, military, communication, transportation, education, etc.

#### Available Models:


DS-7304HQHI-SH, DS-7308HQHI-SH, and DS-7316HQHI-SH.

#### Main Features:

- Connectable to TVI and analog cameras;
- Connectable to the Coaxitron camera with long transmission distance;
- Connectable to network cameras;
- Simultaneous HDMI, VGA and CVBS outputs, HDMI output and VGA output at up to 1920×1080P resolution.
- New GUI and supports starting record with one key;
- Redundant recording, holiday recording schedule configuration;
- Instant playback for assigned camera during multi-channel live view mode;
- Support up to 16-ch synchronous playback at 1080P resolution; and reverse playback for multi-channel;
- Smart playback to go through less effective information;
- Manual video quality diagnostics;
- Customization of tags, searching and playing back by tags;
- Locking and unlocking record files;
- Support HDD quota and group management; different capacity can be assigned to different cameras under quota mode;
- Provide 4 SATA interfaces and 1 eSATA interface for record and backup;
- 1 self-adaptive 10M/100M/1000M network interface;
- Support access by EZVIZ Cloud P2P;
- Support Hikvision DDNS (Dynamic Domain Name System);
- Network detection function.




#### Physical Interfaces:



Index	Name
1	VIDEO IN
2	VIDEO OUT
3	AUDIO IN, RCA Connector
4	USB Port
5	HDMI Interface
6	VGA Interface
7	CVBS AUDIO OUT and VGA AUDIO OUT
8	LAN Network Interface
9	RS-485 Serial Interface, Keyboard Interface, ALARM IN and ALARM OUT
10	100~240V AC Power Input
11	Power Switch
12	GND
13	LINE IN
14	eSATA Interface
15	RS-232 Serial Port

#### Typical Application:



## Specifications:

Model	DS-7304HQHI-SH		DS-7308HQHI-SH		DS-7316HQHI-SH	
Video/Audio input	Video compression	H.264				
	Analog and HD-TVI video input	4-ch (up to 6-ch)		8-ch (up to 10-ch)		16-ch (up to 18-ch)
		BNC interface (1.0Vp-p, 75 Ω)				
	Supported camera types	720P/25, 720P/30, 720P/50, 720P/60, 1080P/25, 1080P/30, CVBS				
	IP video input	2-ch				
		Up to 2MP resolution				
	Audio compression	G.711u				
	Audio input	4-ch, RCA (2.0 Vp-p, 1 KΩ)				
Two-way audio in	1-ch, RCA (2.0 Vp-p, 1 KΩ)					
Video/Audio output	HDMI / VGA output	1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz				
	CVBS output	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480				
	Encoding resolution	Main stream: 1080P / 720P / VGA / 4CIF / CIF				
		Sub-stream: WD1 (non-real-time) / 4CIF(non-real-time) / CIF / QCIF / QVGA				
	Frame rate	Main stream: 1/16 fps ~ Real time frame rate				
		Sub-stream: 1/16 fps ~ Real time frame rate				
	Video bitrate	32 Kbps-10 Mbps				
	Audio output	2-ch, RCA (Linear, 1KΩ, for VGA output and CVBS output respectively)				
	Audio bitrate	64 Kbps				
	Dual-stream	Support				
	Stream type	Video, Video & Audio				
Synchronous playback	4-ch		8-ch		16-ch	
Playback resolution	1080P / 720P / VGA / WD1 / 4CIF / CIF / QVGA / QCIF					
Network management	Remote connection	128				
	Network protocols	TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS				
Hard disk	Type	4 SATA interfaces for 4 HDDs; 1 eSATA interface				
	Capacity	Up to 6 TB capacity for each disk				
External interface	Network interface	1; 10M / 100M / 1000M self-adaptive Ethernet interface				
	Serial interface	RS-232, RS-485, Keyboard				
	USB port	3 × USB2.0				
	Alarm in / out	16 / 4				
General	Power supply	100 ~ 240VAC, 47 ~ 63HZ				
	Consumption (without hard disks)	≤ 30W	≤ 40W		≤ 55W	
	Working temperature	-10 °C ~ +55 °C (14 °F ~ 131 °F)				
	Working humidity	10% ~ 90%				
	Chassis	19-inch rack-mounted 1.5U chassis				
	Dimensions (W × D × H)	445 × 390 × 70 mm (17.5 × 15.3 × 2.7 inch)				
	Weight (without hard disks)	≤ 5Kg (11.0lb)				